

SAFETY DATA SHEET
FOR COATINGS, RESINS, AND RELATED MATERIALS
DATE OF PREPARATION - 01-01-2014
Prepared by: Compliance Dept.

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: Munro Products
DISTRIBUTOR: 9150 Clarence Center Road
Clarence Center, NY 14032

INFORMATION: 716/741-9450
EMERGENCY: **CHEMTREC® 1-800-424-9300**

PRODUCT CLASS: FILLER
TRADE NAME: **BathWorks DIY White High Speed Filler**

CODE: BW-FILLER

SECTION II - HAZARDOUS INGREDIENTS

COMMON NAME	ACGIH TLV (PPM)	OSHA PEL (PPM)	CHEMICAL NAME
UNSATURATED POLYESTER RESIN	5 mg/m3	5 mg/m3	
STYRENE MONOMER	50	100	
MAGNESIUM SILICATE	20 mpppf	20 mpppf	
BARIUM SULFATE	NE	NE	
TITANIUM OXIDE	10 mg/m3	15 mg/m3	

SECTION III - PHYSICAL DATA

BOILING POINT: NA **SPECIFIC GRAVITY:** 1.71
VAPOR PRESSURE: NA **MELTING POINT:** NA
VAPOR DENSITY: NA **EVAPORATION RATE:** Less than 1
SOLUBILITY IN WATER: Slight
APPEARANCE AND ODOR: White thick paste with typical styrene odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 100 F SFCC **FLAMMABLE LIMITS:** NA
LEL: NA **UEL:** NA
EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical, water fog.
SPECIAL FIRE FIGHTING PROCEDURES: : NA

UNUSUAL FIRE AND EXPLOSION HAZARDS: Styrene will polymerize at elevated temperatures of fire conditions. If this occurs in a closed container, there is a possibility of violent rupture.

SECTION V - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: (X) INHALATION (X) SKIN (X) INGESTION
HEALTH HAZARDS (ACUTE AND CHRONIC): Objectionable odor, eye and nasal irritation, dizziness and drunkenness.
CARCINOGENICITY: (X) NTP (NA) IARC (NA) OSHA
SIGNS AND SYMPTOMS: Redness and/or swelling of affected area.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NA
FIRST AID:
EYES: Flush with water for 15 minutes. Contact physician.
SKIN: Wash with mild soap and water.
INHALATION: Remove from contamination to fresh air.
INGESTION: DO NOT INDUCE VOMITING.

SECTION VI - REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Uncontrolled reactions with peroxides.
INCOMPATIBILITY: Strong acids, peroxides, and oxidizing agents.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NA
HAZARDOUS POLYMERIZATION: May Occur.
CONDITIONS TO AVOID: Sunlight, open flame, contamination.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Absorb with inert materials and place in closed containers.
WASTE DISPOSAL METHOD: Burn in an adequate incinerator or bury in an approved landfill in accordance with applicable laws.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in ambient temperature in a well ventilated area away from excessive heat or open flame.
OTHER PRECAUTIONS: Avoid breathing vapors

SECTION VIII - PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: NA
VENTILATION: Local Exhaust recommended. Mechanical good general ventilation.
PROTECTIVE GLOVES: Polyethylene or rubber.
EYE PROTECTION: Safety glasses with side shields.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Clean clothing covering body.
WORK/HYGIENE PRACTICES: Practice good hygiene and use with caution to avoid eye and skin contact.
TUB REFINISHING, INC. DBA MUNRO PRODUCTS

NON WARRANTY

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. No warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use is beyond our control. No suggestion for product use, nor anything contained herein, shall be construed as a recommendation for its use in infringement of any existing patent, and Munro assumes no responsibility or liability for operations that do infringe any such patents.

TUB REFINISHING, INC. DBA MUNRO PRODUCTS