MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS **DATE OF PREPARATION - 01-03-2009**

Prepared by: Compliance Dept.

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: Tub Refinishing, Inc

DISTRIBUTOR: 9150 Clarence Center Road

Clarence Center, NY 14032

INFORMATION: 716/741-9450

CHEMTREC® 1-800-424-9300 **EMERGENCY:**

SLIP GUARD ADDITIVE PRODUCT NAME: **BathWorks Fine Grit TRADE NAME:**

Slip Guard Additive CODE:

SECTION II - HAZARDOUS INGREDIENTS

COMMON NAME CHEMICAL NAME

POLYPROPYLENE PIGMENT 1-PROPENE HOMOPOLYMER POLYOLEFINS CAS #9003-07-0

HMIS+

and Flattening Agents

Polypropylene Texturing Pigment

Health hazard: Flammability hazard:

1 Slight Reactivity hazard: 0 Minimal

RATING

0 Minimal

APPEARANCE AND ODOR: White particulate; odorless

Hazardous Ingredients Recommended Atmosphere Levels**

Polyproylene 10mg/m total 5mg/m respirable

Our supplier interprets the U.S. Occupational Safety and Health Act and Regulations, including the Hazard Communication Standard 29 CFR 1910.1200 dated November 25, 1983, this product should NOT be considered a health hazard material.

SECTION III - PHYSICAL DATA

BOILING POINT: NA VAPOR PRESSURE @ 20 degree C: NA

VAPOR DENSITY: Negligible at 20 degree C % VOLATILE (vol.): N / A

FREEZING POINT: SOLUBILITY IN WATER: Negligible

SPECIFIC GRAVITY: 0.9 pH: NA

EVAPORATION: NA

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

CAUTION! MAY FORM FLAMMABLE DUST-AIR MIXTURES.

FLASH POINT: 276 degree C (530 degree F) COC, ASTM D57-92

AUTOIGNITION TEMPERATURE : Not determined

EXTINGUISHING MEDIA: Water spray, dry chemical, foam, carbon dioxide or halon.

SPECIAL FIRE-FIGHTING PROCEDURES: None

UNUSUAL FIRE & EXPLOSION HAZARDS: May form flammable dust-air mixtures.

Stable STABILITY CONSIDERATIONS:

INCOMPATIBILITY WITH: Avoid contact with hot or concentrated nitric and perchloric acids, fuming

sulfuric acid or 98% sulfuric acid at 60 degrees C (140 degree F) or above.

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS PRODUCTS OF COMBUSTION: Combustion products depend on temperature, other materials present and air supply. They can be carbon monoxide, carbon dioxide, acrolein, formaldehyde, other aldehydes, ketones, fatty acids, methane, ethane and unsaturated hydrocarbons. Carbon

monoxide is the most prominent.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION V - HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF OVEREXPOSURE IN THE WORKPLACE:

None known

Not

EMERGENCY AND FIRST AID PROCEDURES: Not applicable.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

Known

PRIMARY ROUTE OF ENTRY: Inhalation

Not evaluated for carcinogenicity by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program) or the OSHA (Occupational Safety & Health Administration). There is no evidence of carcinogenicity in any animal species.

REPORTED HUMAN EFFECTS: None known **REPORTED ANIMAL EFFECTS:** None known

SECTION VI - SPECIAL PRECAUTIONS AND ADDITIONAL COMMENTS

SPECIAL NOTATION:

Munro Products, BathWorks, TubWorks & Tub Refinishing, Inc. are not responsible for accidents related to the application of the slip guard products on bathtubs, shower bases or other areas needing the slip guard application. The customer should test, maintain and care for all slip guard areas through the life time of the slip guard application. Special attention, caution and maintenance is recommended.

NON WARRANTY

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. No warranty or quarantee expressed or implied is made regarding the performance of any product, since the manner of use is beyond our control. No suggestion for product use, nor anything contained herein, shall be construed as a recommendation for its use in infringement of any existing patent, and Munro assumes no responsibility or liability for operations that do infringe any such patents.

TUB REFINISHING, INC. DBA MUNRO PRODUCTS

^{**}Air level recommended by our supplier.