

IMPORTANT:

Please read through the instructions carefully before starting project Scan the QR code inside this booklet to find helpful project tutorial videos!

SUPPLIES INCLUDED

Part A - Paint (8oz)

Liquid Primer (2oz)

EZ-Etch (4oz) Scrubbing Pad

Stir Stick

Mini Paint Trav

Part B - Hardener (2oz) • 2" High Density Foam Roller & Handle Liquid Primer (2oz) • 1" Foam Brush

 Wet/Dry Sandpaper (120 grit) Instructions (with Safety Warnings & Care Tips)

RECOMMENDED SUPPLIES (NOT INCLUDED)

Protective Surface Coverings • Hair Dryer or Wet-Vacuum

Blue Painters Tape

Paper Towels

Razor Blade or Scrapers Comet® or Ajax®

Respirator Any other items you may feel necessary depending on your situation.

Ventilator Fan 100% Silicone Caulk

Garbage Bag

Protective Eyewear

For all cast iron, steel, & ceramic fixtures - Bathworks® EZ Etch Kit is strongly recommended. If unsure, do not paint, and return kit unopened.

SAFETY & CLEAN UP

Liquid products found within this kit are solvent-borne and are highly flammable. Care should be taken to avoid the inhalation of spray mist or vapors, as well as contact between the wet paint and exposed skin or eyes. Always keep work areas well ventilated and wear personal protective equipment - respirator, eyewear, & gloves. Keep away from flame, children, animals, and individuals sensitive to fumes. Always ensure nearby surfaces are covered and protected. Cleaning solvent for this paint is Lacquer Thinner or a similar substitute. In the event of spills, ensure that Lacquer Thinner is appropriate and safe to use on intended surfaces as there's a risk of serious and permanent damage to surfaces such as linoleum, plastics, wood and anything previously painted. See additional safety notes at the end of this document.

DIRECTIONS

NOTE: This kit may be used for bathtubs, tile, wall surrounds, sinks, & more!

STEP 1: Clear the sink of all personal items. Make sure there is positive air-flow and adequate ventilation in the work areas at all times. <u>CLEAN SINK THOROUGHLY!</u> Scrub sink with Ajax® or Comet® while focusing on areas with heavy soap buildup - use steel wool if needed.

NOTE: <u>ANY</u> soap residue present will prevent bonding and cause failure.

OPTIONAL: Use a razor blade or sharp scraper to remove the caulk around the sink. You may or may not elect to do this dependent upon individual situations. Not necessary, but recommended.

NOTE: <u>NEVER</u> place tools on unprotected surfaces. Keep bag nearby to collect debris, foreign materials, and waste while working on this project.

CAUTION: In the following steps, proper ventilation and personal protection (gloves & eyewear) are highly recommended. Sink drains and faucets should be covered until the rinsing stage in the following step.

NOTE: It is natural for contents of EZ-Etch to settle over time, shake extremely well before use.

STEP 2: Pour the entire container of **EZ-Etch** into the center of the sink. Using the provided **Scrubbing Pad**, thoroughly spread to the entire surface. Allow the product to rest for **20 minutes**. Rinse well with the scrubbing pad and water (may be water from the sink or a nearby bucket.) While the sink is still damp, sand the sink completely using **Wet/Dry Sandpaper** provided. Rinse well after sanding.

STEP 3: Place a glove or plastic bag over the sink faucet and handles to avoid water dripping into the sink. Using a blow dryer or wetvacuum, blow water out of drain and handle areas. When the surfaces are free of moisture, use blue painters tape to mask off the sink drain and the counter around the sink.

NOTE: <u>ANY</u> moisture while rolling paint may result in product failure and cause bonding issues.

STEP 4: Use a paper towel to remove any foreign materials or debris that may be in the sink area. If any structural repairs are needed, they may be done at the completion of this step.

CAUTION: In the following steps - proper ventilation, gloves, and eye wear are strongly recommended. Use paint products with caution.

STEP 5: Empty the contents from the bottle labeled **Liquid Primer** into a paper towel. Using that paper towel, wipe entirely across any surface desired that will be refinished in the following steps. Dispose of moist paper towel in a plastic bag and close it to minimize fumes. Allow primer to dry on the surface for **5 minutes**.

STEP 6: Retrieve **Part A: Paint & Part B: Hardener** from your kit. Empty the contents from the Part B container into the Part A container. Mix thoroughly for **3 minutes** with the provided **Stir Stick** until completely dispersed. Exercise caution as to not create air bubbles while mixing. Allow mixed paint to sit for **5 minutes**. Empty mixture into **Paint Tray** when completed.

NOTE: The "pot-life" for this product mixture is approximately **3** hours (at 70° F) - this is the time frame you have to complete the project before the mixed paint becomes unusable. Mix ratio for this product is **4:1** (4 parts A to 1 part B.)

STEP 7: Using the provided **Foam Brush**, utilize a dabbing technique to apply paint around all handles and areas where a roller will not fit. Next, using the provided **Foam Roller**, apply paint to the bottom of the sink and work your way up the curves of the surface. Finally, roll the top edge of the sink.

NOTE: Remember to use a fair amount of paint material while rolling. Too much paint will result in runs & sags. Too little paint will lead to a "dry-roll" result and cause product failure. **This is very important.**

OPTIONAL: A second coat may be applied right away following the same pattern. Ensure that you do not lean on wet surfaces.

STEP 8: After allowing coating to set for **45 minutes**, carefully remove the tape by pulling at a 45° angle. Please allow refinished surfaces to dry **24 hours** before use. If caulk was removed before refinishing, reapply around the sink using 100% silicone caulk once surfaces are dry. Allow caulk to dry, and rinse refinished surfaces with warm water before use.

NOTE: Dispose of all unused materials and debris immediately after completing the project. Obey all town, city, state, national, & international codes for proper paint disposal.

THANK YOU FOR CHOOSING

BathWorks[®] REFINISHING PRODUCTS

We want to hear about your experience!

Please scan the QR code below with the camera app on your smartphone to find links to our product listings to leave a review on the platform you purchased your kit from.

If you're pleased with the results.. tell others!

If not, tell us!

We welcome any questions and provide troubleshooting for concerns on any project.

Give us a call at **1.800.872.8827**Or email us at **info@munroproducts.com**



Please enjoy 10%* off your next total purchase made on our website:

bath-works.net

Using coupon code:

DIY10

*Standard exclusions apply. 10% off total Bathworks® order. Offer valid only at https://www.bath-works.net. May not be used in conjunction with any other coupon. Employees not eligible for discount. This offer may be modified by Tub Refinishing Inc, DBA Munro Products, in its sole discretion without notice at any

SURFACE CARE TIPS

Congratulations!

Your bathtub or bath fixture has just been resurfaced with the finest product in the tub and tile coating industry.

> Follow these care tips to maintain the beauty of your surface.

GENERAL TIPS

- Treat as if this is a brand new fixture; remove excess water and wipe dry after each use.
- Always be certain faucets are tightly closed and the shower pipe is drained after each use.
- DO NOT rest any soap bottles, spray cans, or wet clothes on the surface for extended periods of time.
- **NEVER** use hair dye in a refinished fixture.
- If bathing pets in the sink, always place a towel down to prevent scratches.

BATHMATS

- If you do not have the non-slip system applied to your surface and you find it to be to slippery, you may use a <u>NON-SUCTIONED</u> bathmat or a towel (these must be picked up after each use.) Do not hang the mat or towel over the bathtub.

 • Use of a suctioned bathmat or stick-on strips will cause failures
- of the resurface coating.

CLEANING

- Even though the fixture does not look dirty, it should be cleaned at least once a week with a liquid NON-ABRASIVE cleaner (Scrubbing Bubbles®, 409®, or Fantastic® are recommended products.)
- NEVER use bleach or abrasive cleaners (Ajax®, Comet®, or Soft Scrub®) on a refinished surface. If the non-slip protection system is applied to the bottom of your bathtub, you may use Soft Scrub® on that area if needed.
- **DO NOT** use Mr. Clean Magic Eraser® on your refinished surface. This is a micro-abrasive sandpaper sponge and will damage your coating over time with repeated use.

Remember

If you treat your new surface with respect, clean it regularly, and keep your taps dry - your tub will stay beautiful and radiant for years to come! Use Bathworks® Cleaner and Polishing Kit for the ultimate shine and protection!

LIMITED WARRANTY

Tub Refinishing, Inc. DBA Munro Products as follows; this warranty is in lieu of all other written or unwritten, expressed, or implied warranties, and Tub Refinishing, Inc. DBA Munro Products expressly disclaims any warranty of merchantability or fitness for a particular purpose. The buyer assumes all risks whatsoever as to the use of the material. Keep away from children, animals, or persons that are sensitive to paint or fumes. Fumes can be harmful to humans and animals, and can also be flammable.

SAFETY

A protective respirator should be worn if available. Use product with adequate ventilation. Always use rubber gloves. Tub Refinishing, Inc. DBA Munro Products is not responsible for accidents or misuse of these products or parts and materials of this kit. Safety is in the hands of the user. Keep all refinishing kit materials and tools away from children, animals, and individuals sensitive to paint or furnes. Some items in this kit are flammable and should be disposed of properly in accordance to local state, city, & town codes regulating used paint products. Use all paint products with caution. DO NOT dispose of paint or clean tools by using water and flushing down household drains - these are solvent-borne products and may potentially damage pipes & the environment. Use Lacquer Thinner or comparable cleaner for cleaning tools & spills. Lacquer Thinner is capable of permanently damaging surfaces such as linoleum, plastic, wood, and previously painted surfaces. Never use Lacquer Thinner on skin and use gloves & eyewear while using. If you are unsure about the use or safety of this product, please return the unopened and unused kits to the supplier. All returned goods are at the purchaser's cost. Opened or used materials will be refused for credit. See all Safety Data Sheets (SDS) which are available via our website: bathworks.net

SUITABILITY FOR USE

The user is responsible for establishing that these products are suitable for the user's application and that all requirements for meeting approvals, standards, codes, disposal, use, and regulations of any kind are satisfied. Distributor denies any responsibility for establishing suitability of use; where, when, and how the materials from this kit are used. Read all information and instruction before use of this product. Use caution.

FOR EMERGENCY: CHEMTREC® 1-800-424-9300



America's #1 Choice in Bathroom Restoration For Over 50 Years!

Find us on Facebook & Instagram at bathworks.kits

Tub Refinishing, Inc. DBA Munro Products, and Bathworks®. Bathworks® is an exclusive trademark of this company.

bath-works.net info@munroproducts.com 1.800.872.8827